

# Emerging Pretreatment Technologies for Enhanced Bioenergy Production from Organic Waste

**Cigdem Eskicioglu, Ph.D, P.Eng.**

Associate Professor

Leader, UBC Bioreactor Technology Group

University of British Columbia, Okanagan Campus

School of Engineering, 1137 Alumni Avenue, Kelowna, Canada, V1V 1V7

cigdem.eskicioglu@ubc.ca

Increasingly, energy sustainability concerns all around the world bring renewable energy sources to the forefront. Among renewable sources, the development of energy efficient biomass-to-biofuel processes can replace fossil fuel use and reduce greenhouse gas emissions. In particular, municipal and industrial wastewater treatment residues (waste sludge) and lignocellulosic agricultural crops waste have a very significant unutilized energy potential. When landfilled, waste sludge can decompose in an uncontrolled environment and can contribute to greenhouse gas emissions. Similarly, lignocellulosic biomass is abundant all year around and the remaining portion after used as animal feed is often burnt in open environment that can further cause environmental concerns [1, 2].

Bioreactor processes, such as anaerobic digestion and dark fermentation have been extensively studied for their ability to convert a wide variety of organic waste including waste sludge, animal manure and lignocellulosic biomass to methane [3] and biohydrogen [4]. The bottleneck of conventional anaerobic digestion is slow degradation of the municipal waste activated sludge (WAS), comprised of a mixture of different microbial cells, organic and inorganic compounds that adhere together with extracellular polymeric substances (EPS). This necessitates long retention time (20-30 days) requiring large digester volume which eventually leads to high capital cost [5]. Similarly, complex structure of lignocellulosic biomass, comprised of holocelluloses (cellulose, hemicelluloses) and lignin, allows for limited accessibility to the biodegradable organics (i.e. holocelluloses). Such limited accessibility causes methane/hydrogen yields significantly lower than the theoretical estimations based on biomass compositional/structural features [6, 7].

Therefore, research at UBC's Bioreactor Technology Group in the last 10 years has focused on various pretreatment technologies using mechanical, chemical, thermal (i.e. conductive, microwave, and radio frequency), and biological ways or combinations to disintegrate polymeric network of wastewater sludge and dissolve lignin (delignification) in lignocellulosic waste for better enzymatic hydrolysis/microbial degradation [8-10]. These pretreatment technologies applied prior to anaerobic digestion and/or dark fermentation can enhance the rate and the extent of biogas and/or biohydrogen production resulting in smaller bioreactors.

The primary focus of this keynote presentation will be the performance evaluation on the aforementioned pretreatment technologies applied on various organic waste for enhance bioenergy recovery and improved digestate (final product) for final disposal (i.e. land application as soil amendment). The secondary focus will be on fate and transformation of emerging micro- (i.e. hormones, antimicrobials, pharmaceuticals), and nano-contaminants (i.e. ZnO) in the conventional and advanced anaerobic sludge digesters incorporating these pretreatment technologies.

## References

- [1] A. Palacios-Orueta, E. Chuvieco, A. Parra and C. Carmona-Moreno, "Biomass burning emissions: A review of models using remote-sensing data," *Environmental Monitoring and Assessment*, vol. 104, pp. 189-209, 2005.
- [2] L. Bhatia, S. Johri and R. Ahmad, "An economic and ecological perspective of ethanol production from renewable agro waste: a review," *AMB Express*, vol. 2, no. 65, pp. 1-19, 2012.
- [3] C. Sawatdeenarunat, K. Surendra, D. Takara, H. Oechsner and S. Khanal, "Anaerobic digestion of lignocellulosic biomass: Challenges and opportunities," *Bioresource Technology*, vol. 178, pp. 178-186, 2015.

- [4] A. Singh, S. Sevda, I. Abu Reesh, K. Vanbroekhoven, D. Rathore and D. Pant, "Biohydrogen production from lignocellulosic biomass: Technology and Sustainability," *Energies*, vol. 8, pp. 13062-13080, 2015.
- [5] L. Appels, J. Baeyens, J. Degreve and R. Dewil, "Principles and potential of the anaerobic digestion of waste-activated sludge," *Prog. Energy Combust. Sci.*, vol. 34, pp. 755-781, 2008.
- [6] F. Monlau, C. Sambusiti, A. Barakat, X. Guo, E. Latrille, E. Trably, J.-P. Steyer and H. Carrere, "Predictive models of biohydrogen and biomethane production based on the composition and structural features of lignocellulosic materials," *Environmental Science and Technology*, vol. 46, no. 21, pp. 12217-12225, 2012.
- [7] H. Carrere, G. Antonopoulou, R. Affes, F. Passos, A. Battimelli, G. Lyberatos and I. Ferrer, "Review of feedstock pretreatment technologies for improved anaerobic digestion: From lab-scale research to full-scale application," *Bioresource Technology*, vol. 199, pp. 386-397, 2015.
- [8] N. Mehdizadeh, C. Eskicioglu, J. Bobowski and T. Johnson, "Conductive heating and microwave hydrolysis under identical heating profiles for advanced anaerobic digestion of municipal sludge," *Water Research*, vol. 47, pp. 5040-5051, 2013.
- [9] M. Saha, C. Eskicioglu and J. Marin, "Microwave, ultrasonic, and chemo-thermal pretreatments for enhancing methane potential of pulp mill wastewater treatment sludge," *Bioresource Technology*, vol. 102, no. 17, pp. 7815-7826, 2011.
- [10] A. Wahidunnabi and C. Eskicioglu, "High pressure homogenization and two-phased anaerobic digestion for enhanced biogas conversion from municipal waste sludge," *Water Research*, vol. 66, pp. 430-446, 2014.